

## Product description

Thickening additive belonging to the range of additives to be used in addition to RESIN 3+, to obtain compounds with different characteristics. Ideal for gluing, creasing and large imperfections. It can be used for applications above and below the waterline. It can be mixed with the other additives of the system, improving the spreadability and appearance of the final product.

## Product description

Product code	W6715		
Colour	White .001		
Solids (by volume)	ASTM D2369		100%
Packaging	0,75 Lt		

## Application and use

### APPLICATION PROCEDURE

Add the additive to RESINA 3+ only after carefully mixing component A and component B in a 2:1 ratio.

Gluing and laminating: Mix 2 parts of catalyzed RESINA 3+ + 1 part of R-Silicies to obtain a fluid compound for small gluing and laminations.

Cords, grouting, fixing: Mix 1 part catalyzed RESINA 3+ + 1 part R-Silicies to obtain a paste suitable for creasing, general grouting and accessory fixing.

Large grouts and creases: Mix 1 part of catalyzed RESINA 3+ + 2 part of R-Silicies to obtain a structural compound suitable for large grouts and large creases.

## Storage

It is recommended to avoid exposure to air and extreme temperatures. To maximize the shelf life in the can, it is worth checking that the container is well closed during the storage and the temperature is between 10° C and 35° C. Avoid exposure to direct sunlight.

## Safety rules

---

Comply with the provisions set by the local health and safety at work regulations. Avoid contact with the skin, for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application, use appropriate protections (masks, gloves, glasses, etc.). Before using, read sections 7-8 of the SDS.

### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by conferring them in a recycling center. Packages containing the unused products: Dispose of the unused product in accordance with the law of disposal of such waste, for example by recycling it in a recycling center, recycling of packaging is prohibited in this case. Do not empty into drains or watercourses. Product packaging must be kept indoor, and the temperature in the storage place must be between 10° C and 35 °C. Do not expose to sunlight.

## Notes

---

The values indicated in the present technical sheet can have slight variations from one batch to another.

The applied product must not come in contact with water, chemicals or be subjected to mechanical stress before the curing is complete. Wet film thicknesses refer to a product that has not been diluted. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experience; however, since the product is predominantly used outside the manufacturer's control. Boero Bartolomeo S.p.A can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other precedent to this one.