

Diluyente 6380

Code: 6380.000

THINNER FOR GUMMIPAIN LINE

CHARACTERISTICS

Thinners are volatile liquids used to dissolve paint components, reduce the viscosity and aid paint application. Suitable film formation depends on proper thinner evaporation, therefore the correct use of thinners is very important in order to achieve good paint application. Thinner 6380 is suitable for Gummipaint® and Gummipaint® A/F, for brushing and spraying applications.

TECNICAL DATA

Curing mechanism:	
Specific weight:	0,83 ± 0,02 Kg/L
Solid By Volume:	
Flash Point:	+0 °C
Appearance:	
Colour:	
Packaging:	0,50 litres

SURFACE PREPARATION

APPLICATION

For brushing applications use Thinner 6380 to maximum 5-10%. For spraying applications use Thinner 6380 as it follows:- 40 - 50% con Gummipaint - 20 - 30% con Gummipaint A/V

Diluyente 6380

Code: 6380.000

THINNER FOR GUMMIPAIN T LINE

APPLICATION DATA

Drying time before use (20 °C):

Pot Life (20 °C):

Application temp. min/ max:

Hardener:

Mixing ratio by volume:

Mixing ratio by weight:

Thinner/Thinner for cleaning:

Wet film thickness per coat:

Dry film thickness per coat:

Theoretical coverage per coat:

Minimum covering time (20 °C):

Maximum covering time (20 °C):

Number of coats:

NOTES

SAFETY RULES

This product is a volatile liquid which can ignite if exposed to a naked flame, spark or electric charges also at temperatures below 21°C. Keep containers well sealed and far from naked flames, sparks and any source of heat. Do not leave containers in full sunlight. Adequate ventilation must be provided in secluded areas where the product is stored or handled. Avoid contact with the skin and do not inhale. Before use read the sections 7-8 of the Safety Data Sheet (MSDS). INSTRUCTIONS FOR THE SAFE BIOCIDAL PRODUCT DISPOSAL AND PACKAGING Empty packaging having contained biocidal products: empty packaging shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre. Packaging containing unused biocidal product: the unused product shall be disposed of in compliance to provisions required by the law on disposal of said waste, for example by consignment to a recycling centre, in this case it is forbidden to recycle packaging. Do not empty into drains and watercourses. The paint cans must not be stocked outside and must be stored at a temperature between 10 ° C and 35 ° C. Do not expose to the sun.

DISCLAIMER The information in this data sheet is based on accurate laboratory tests and practical experience, which guarantee the quality of the product if used according to our recommendations. The data contained herein are liable to modification as a result of continuous product development. We do not accept any liability arising from use not in accordance with our recommendations, unless authorized specifically by the Veneziani Technical Services. This edition annuls and replaces all previous issues.