

# TEAK 2

## TECHNICAL DATA SHEET

### Product description

---

Sunlight , salt and pollution tend to make the teak grey in a short time, depriving it of the exotic charm that only this essence can give. The treatment with Teak 2 restores the original colour of the wood.

### Product information

---

Colour	Colourless .001	
Specific gravity	UNI EN ISO 2811-1	1,00 ÷ 1,05 g/cm <sup>3</sup>
Packaging	1 Lt	

### Application and use

---

#### **APPLICATION PROCEDURE**

Protect the painted areas. Wet the wood, pour TEAK 1 on the surface and, with a soft brush or a sponge, gently scrub following the wood grains until you obtain a dark colour. Rinse and repeat the same operation with Teak 2 until you reach a yellow-gold colour.

### Storage

---

It is recommended to avoid exposure to air and extreme temperatures. To maximise the shelf life in the can, it is worth checking that the container is well closed during the storage and that temperature is between 10° C and 35° C. Avoid exposure to direct sunlight.

# TEAK 2

## TECHNICAL DATA SHEET

### Safety rules

---

Observe the provisions of DPR 303 and 547. Avoid the contact with the skin for example. Operate in well ventilated places and, if in closed areas, use vacuum cleaners, fans and air conveyors. During the application, use appropriate protections (masks, gloves, glasses, etc). Before using, read section 7-8 of the SDS.

#### INSTRUCTIONS FOR THE DISPOSAL OF PRODUCTS AND PACKAGING

Empty packaging that contained products: Dispose of empty packaging according to the requirements of the waste disposal law, for example by taking them to the recycling centre.

Packages containing the unused products: Disposal of the unused product in accordance with the law of disposal of such waste, for example by taking it to a recycling centre; recycling of packaging is prohibited in this case. Do not empty into drains or water courses. Product packaging must be kept indoor and temperature in the storage place must be between 10° C and 35 °C. Do not expose to sunlight.

### Notes

---

The values indicated in the present technical sheet can have slight variations from one batch to another. The applied product must not come in contact with water, chemicals or be subjected to mechanical stress before curing is complete. The wet film thicknesses refer to the non-diluted product. With dilution, this value will rise. The above information is the result of accurate laboratory tests and practical experiences; however, since the product is predominantly used outside the manufacturer's control, Boero Bartolomeo S.p.A. can only guarantee its quality. The information contained in this sheet may be subject to revision by the Company. For clarification, updates or for further information, it is recommended to contact Boero Bartolomeo S.p.A directly. The present datasheet annuls and replaces every other to this one.